

PRODUCT DATASHEET


Type: ET-DUO-PLUS-S-2000-W
Art. Nr.: 46140



9120105419666

Short description

Convector storage heater, stone, white, 2000W, 230V

**Product Description**

The ETHERMA DUO PLUS S convector storage heater is a modern direct heating appliance that impresses in three ways when it comes to heating technology: the unique combination of convection, radiant heat and heat storage not only promises increased performance, but also optimized operating costs. The powerful heater saves space thanks to its compact design and at the same time generates pleasant radiant heat. It is particularly suitable for large rooms as efficient transitional heating or as an ideal replacement for outdated night storage heaters. The heater can be mounted horizontally on the wall and is connected via a connecting cable with plug. NEW: The DUO PLUS S has a switch with the stages Off / without internal control / with internal control. The position without internal control is selected if the DUO PLUS S is controlled via an external room thermostat. Make sure you use a room thermostat that complies with the Ecodesign. Functions in the position with internal control: In the event of a sudden drop in temperature, e.g. due to an open window, the appliance switches off automatically. In addition, the DUO PLUS S can be individually adapted to the respective requirements via daily and weekly programs. The frost protection mode of the appliance is active when the control is in the off state. The heater can be mounted horizontally on the wall and is connected via a connecting cable with plug. Surface: 12 mm coated silicon brick; Protection class: IP 24; Mounting depth: 105 mm; Control range: 15-28 °C; Frost protection function: 7 °C; Surface temperature: max. 85 °C; Connection cable: 1 m incl. plug; 230 V, System design: CE-compliant

ETIM characteristics

Model	Standard	Heating capacity	2000 Watt
Mounting method	Wall model	Supply voltage	230 230 Volt
Material front	Other	Frequency supply voltage	50 50 Hertz
Grid model	Fins	Length connection cord	1 Metre
Material heating element	Other	Number of switch positions	2
Air exhaust	Top	Temperature adjustment	15 28 Degrees celsius
With fan	✗	Differential gap, temperature	0.1 Degrees celsius
Electrical connection	Connection cable with plug	Width	1000 Millimetre
Position control panel	Top	Height	500 Millimetre
Suitable for wireless remote control	✗	Depth	105 Millimetre
With remote control	✗	Weight	22 Kilogram
Power control	Electronic		
Colour	White		
Degree of protection (IP)	IP24		
Protection class according to IEC 61140	II		
With overheating protection	✓		
Programmable	✓		
Frost protection circuit	✓		
Digital indication	✓		
With presence detector	✗		
Suitable for bus connection	✗		

Created on: 09/10/2024

PRODUCT DATASHEET

With time switch clock	✓
Adaptive (self-learning)	✗
Consumption indication	✗
Open window detection	✓
Compatible with Apple HomeKit	✗
Compatible with Google Assistant	✗
Operation by app	✗
Compatible with Amazon Alexa	✗
IFTTT support available	✗
Number of supported pilot wire commands	None

Created on: 09/10/2024

PRODUCT DATASHEET



Type: ET-DUO-PLUS-S-1500-W
Art. Nr.: 46139



9120105419659

Short description

Convector storage heater, stone, white, 1500W, 230V

**Product Description**

The ETHERMA DUO PLUS S convector storage heater is a modern direct heating appliance that impresses in three ways when it comes to heating technology: the unique combination of convection, radiant heat and heat storage not only promises increased performance, but also optimized operating costs. The powerful heater saves space thanks to its compact design and at the same time generates pleasant radiant heat. It is particularly suitable for large rooms as efficient transitional heating or as an ideal replacement for outdated night storage heaters. The heater can be mounted horizontally on the wall and is connected via a connecting cable with plug. NEW: The DUO PLUS S has a switch with the stages Off / without internal control / with internal control. The position without internal control is selected if the DUO PLUS S is controlled via an external room thermostat. Make sure you use a room thermostat that complies with the Ecodesign. Functions in the position with internal control: In the event of a sudden drop in temperature, e.g. due to an open window, the appliance switches off automatically. In addition, the DUO PLUS S can be individually adapted to the respective requirements via daily and weekly programs. The frost protection mode of the appliance is active when the control is in the off state. The heater can be mounted horizontally on the wall and is connected via a connecting cable with plug. Surface: 12 mm coated silicon brick; Protection class: IP 24; Mounting depth: 105 mm; Control range: 15-28 °C; Frost protection function: 7 °C; Surface temperature: max. 85 °C; Connection cable: 1 m incl. plug; 230 V, System design: CE-compliant

ETIM characteristics

Model	Standard	Heating capacity	1500 Watt
Mounting method	Wall model	Supply voltage	230 230 Volt
Material front	Other	Frequency supply voltage	50 50 Hertz
Grid model	Fins	Length connection cord	1 Metre
Material heating element	Other	Number of switch positions	2
Air exhaust	Top	Temperature adjustment	15 28 Degrees celsius
With fan	✗	Differential gap, temperature	0.1 Degrees celsius
Electrical connection	Connection cable with plug	Width	1000 Millimetre
Position control panel	Top	Height	500 Millimetre
Suitable for wireless remote control	✗	Depth	105 Millimetre
With remote control	✗	Weight	22 Kilogram
Power control	Electronic		
Colour	White		
Degree of protection (IP)	IP24		
Protection class according to IEC 61140	II		
With overheating protection	✓		
Programmable	✓		
Frost protection circuit	✓		
Digital indication	✓		
With presence detector	✗		
Suitable for bus connection	✗		

Created on: 09/10/2024

PRODUCT DATASHEET

With time switch clock	✓
Adaptive (self-learning)	✗
Consumption indication	✗
Open window detection	✓
Compatible with Apple HomeKit	✗
Compatible with Google Assistant	✗
Operation by app	✗
Compatible with Amazon Alexa	✗
IFTTT support available	✗
Number of supported pilot wire commands	None

Created on: 09/10/2024