

PRODUCT DATASHEET

Type: LAVABATH2-PURE-700-NA
Art. Nr.: 41242



9120105413985

Short description

Bathroom infrared heating panel, metal, grey, 62x160cm, 700W, 230V



*** Image missing:
/Data/Environments/000039/Attachment/Bijlage/PRD/Product/CHR/DE/etherma-db-41242-de.pdf ***

Product Description

The LAVA BATH 2.0 PURE infrared heater blends perfectly into the bathroom with its simple elegance and provides cozy infrared warmth. The two temperature limiters in each panel guarantee safety in use at all times. The innovative technology turns the surface into a very good radiation emitter. In conjunction with the even heat distribution on the surface, the optimally insulated rear guarantees a high degree of radiation efficiency and therefore maximum infrared heat radiation to the front of the room - once switched on, the panel is heated to approx. 80 °C and provides pleasant warmth within a very short time. And thanks to the included, color-coordinated towel holder, it also provides cozy, warm towels. The frameless construction ensures a modern design. There is a choice of three outputs and up to two additional towel rails can be attached to the appliance. The practical Plug & Play box on the back makes it easy to install a control unit, whether directly on the appliance, by radio or using a wired controller. Incl. one closed, powder-coated towel rail, color: traffic white RAL 9016 or nano anthracite RAL 7016, on/off switch, surface temperature: approx. 80 °C, vertical wall mounting, protection class: IP X4, steel housing, plug connection cable: 1 m, test mark: CE compliant.

ETIM characteristics

Type of IR radiation	IR-C	Power consumption	700 Watt
Mounting method	Surface mounting	Supply voltage	230 230 Volt
Mounting direction	Vertical	Frequency supply voltage	50 50 Hertz
Suitable for ceiling mounting	✗	Max. surface temperature	70 Degrees celsius
Degree of protection (IP)	IPX4	Height	1600 Millimetre
Colour	Black	Width	620 Millimetre
With imprint	✗	Depth	52 Millimetre
With room temperature controller	✗	RAL-number	7016
With mounting material	✓	Colour temperature	0 0 Kelvin
With framework	✗		
Material framework	Other		
Colour framework	Other		
Surface treatment	Other		
Surface structure front-side panel	Smooth		
With lighting cove	✗		
Dimmable	✗		
Light outlet	Direct		

Created on: 09/10/2024